TÜVRheinland®

| Scope according to | **Pressure Equipment Safety Regulations 2016 SI 2016 No.: 1105 as amended** |
|---|---|

| Material Manufacturer | | Manufacturing plant | Nationality | Date | Page No.. | |
|---|---|---|---|---|---|---|
| Company Name: | Jay Jagdamba Limited | See Page 11 | India | 20.10.23 | 1 | TUV Rheinland UK Ltd |
| Location: | Office No 405, The Landmark, Plot No. 26A, Sector 07, Kharghar, Navi Mumbai-410 210. Maharashtra, India | | | Rev.: 0 | of : 11 | |

| Cur- | Product grades (Materials-term / Materials-No.) | Product code or standard (Material Specification) | Delivery Cond. | Product Form (Article, Type of Product) | Product dimensions / quantity (Dimensions) Thickness mm from | Thickness mm Up to | ∅ mm from | ∅ mm Up to | Weight max 1=t / 2=kg ⇓ | Weight max result | Technical Specifications Requirements Technical Regulations | Original material manufacturers QMS Certificate / Remarks |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6a | 6b | 7a | 7b | 8a | 8b | 9 | 10 |
| **The use of the materials according to Pressure Equipment Safety Regulations 2016 as amended is bound to the publication of designated standards or to the particular material appraisal. With that the manufacturing reliability for equivalent material grades according to other standards (e.g. BS, AFNOR, ASME) is proved. The requirements and limits of the applicable code respectively the PESR must be observed for the use of material grades listed in column 2 to 4.** | | | | | | | | | | | | |
| 1 | 1.4362; 1.4410; 1.4462; 1.4501 1.4507; 1.4550 | EN 10272 | AT | Ingots | | | | | | | | 9"x11"x52" to 32"x38"x 74" |
| | | | | Billets | | | | | | | | 400mm x 2.5mtr to 600mm x 2.5mtr |
| | | | | RCS | | | | | | | | 80 x 80mm to 200X200mm |
| | | | | Angle | 3 | 12.70 | | | | | | 35x35mm to 120x120mm |
| 2 | 1.4006,1.4057 | EN 10272 | S/QT | Flats | 3 | 60 | | | | | | |
| | | | | Round Bars | | | 3 | 200 | | | | 19.05mm to 152.4mm |
| | | | | Hex/Sq Bars | | | 5 | 100 | | | | 19.05mm to 152.4mm |
| | | | | Threaded Bars | | | 5 | 60 | | | | |
| | | | | Wires | | | 1 | 22 | | | | |
| | | | | HRAP Coils | | | 5 | 32 | | | | Round/Hexagon/Square/Angle/Flat - - Hot Rolled and Bright Bars |

**Remarks**

+AT = solution annealed
+AR = as rolled
+M = thermo mechanical treated
+N = normalized or normalizing formed
+NT = normalized and tempered
+QT = quenched and tempered
+S = soft annealed
+SR = stress relieved

a = PMA for the use in pressure equipment in PESR 2016 as amended neccessary

TÜVRheinland®

| Scope according to | **Pressure Equipment Safety Regulations 2016 SI 2016 No.: 1105 as amended** |
|---|---|

| Material Manufacturer | | Manufacturing plant | Nationality | Date | Page No.. | |
|---|---|---|---|---|---|---|
| Company Name: | Jay Jagdamba Limited | See Page 11 | India | 20.10.23 | 2 | TUV Rheinland UK Ltd |
| Location: | Office No 405, The Landmark, Plot No. 26A, Sector 07, Kharghar, Navi Mumbai-410 210. Maharashtra, India | | | Rev.: 0 | of : 11 | |

| Cur- | Product grades (Materials-term / Materials-No.) | Product code or standard (Material Specification) | Delivery Cond. | Product Form (Article, Type of Product) | Product dimensions / quantity (Dimensions) Thickness mm from | Thickness mm Up to | ∅ mm from | ∅ mm Up to | Weight max 1=t / 2=kg ⇓ | Weight max result | Technical Specifications Requirements Technical Regulations | Original material manufacturers QMS Certificate / Remarks |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6a | 6b | 7a | 7b | 8a | 8b | 9 | 10 |
| **The use of the materials according to Pressure Equipment Safety Regulations 2016 as amended is bound to the publication of designated standards or to the particular material appraisal. With that the manufacturing reliability for equivalent material grades according to other standards (e.g. BS, AFNOR, ASME) is proved. The requirements and limits of the applicable code respectively the PESR must be observed for the use of material grades listed in column 2 to 4.** | | | | | | | | | | | | |
| 3 | 1.4301; 1.4307; 1.4401; 1.4404<br>1.4432; 1.4435; 1.4436; 1.4541<br>1.4571 | EN 10272 | AT | Ingots<br>Billets<br>RCS<br>Angle<br>Flats<br>Round Bars<br>Hex/Sq Bars<br>Threaded Bars<br>Wires<br>HRAP Coils | <br><br><br>3<br>3 | <br><br><br>12.70<br>60 | <br><br><br><br><br>3<br>5<br>5<br>1<br>5 | <br><br><br><br><br>200<br>100<br>60<br>22<br>32 | | | AD 2000 W2<br>AD 2000 W10 | 9"x11"x52" to 32"x38"x 74"<br>400mm x 2.5mtr to 600mm x 2.5mtr<br>80 x 80mm to 200X200mm<br>35x35mm to 120x120mm<br><br>19.05mm to 152.4mm<br>19.05mm to 152.4mm<br><br>Round/Hexagon/Square/Angle/Flat<br>- - Hot Rolled and Bright Bars |

**Remarks**

+AT = solution annealed
+AR = as rolled
+M = thermo mechanical treated
+N = normalized or normalizing formed
+NT = normalized and tempered
+QT = quenched and tempered
+S = soft annealed
+SR = stress relieved

a = PMA for the use in pressure equipment in PESR 2016 as amended neccessary

TÜVRheinland®

| Scope according to | **Pressure Equipment Safety Regulations 2016 SI 2016 No.: 1105 as amended** |
|---|---|

| Material Manufacturer | | Manufacturing plant | Nationality | Date | Page No.. | |
|---|---|---|---|---|---|---|
| Company Name: | Jay Jagdamba Limited | See Page 11 | India | 20.10.23 | 3 | TUV Rheinland UK Ltd |
| Location: | Office No 405, The Landmark, Plot No. 26A, Sector 07, Kharghar, Navi Mumbai-410 210. Maharashtra, India | | | Rev.: 0 | of : 11 | |

| Cur- | Product grades (Materials-term / Materials-No.) | Product code or standard (Material Specification) | Delivery Cond. | Product Form (Article, Type of Product) | Product dimensions / quantity (Dimensions) Thickness mm from | Thickness mm Up to | ∅ mm from | ∅ mm Up to | Weight max 1=t / 2=kg ⇓ | result | Technical Specifications Requirements Technical Regulations | Original material manufacturers QMS Certificate / Remarks |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6a | 6b | 7a | 7b | 8a | 8b | 9 | 10 |
| **The use of the materials according to Pressure Equipment Safety Regulations 2016 as amended is bound to the publication of designated standards or to the particular material appraisal. With that the manufacturing reliability for equivalent material grades according to other standards (e.g. BS, AFNOR, ASME) is proved. The requirements and limits of the applicable code respectively the PESR must be observed for the use of material grades listed in column 2 to 4.** | | | | | | | | | | | | |
| 3 | 1.4301; 1.4307; 1.4401; 1.4404<br>1.4432; 1.4435; 1.4436; 1.4541<br>1.4571 | EN 10272 | AT | Ingots | | | | | | | | 9"x11"x52" to 32"x38"x 74" |
| | | | | Billets | | | | | | | | 400mm x 2.5mtr to 600mm x 2.5mtr |
| | | | | RCS | | | | | | | | 80 x 80mm to 200X200mm |
| | | | | Angle | 3 | 12.70 | | | | | | 35x35mm to 120x120mm |
| | | | | Flats | 3 | 60 | | | | | AD 2000 W2 | |
| | | | | Round Bars | | | 3 | 200 | | | AD 2000 W10 | 19.05mm to 152.4mm |
| | | | | Hex/Sq Bars | | | 5 | 100 | | | | 19.05mm to 152.4mm |
| | | | | Threaded Bars | | | 5 | 60 | | | | |
| | | | | Wires | | | 1 | 22 | | | | |
| | | | | HRAP Coils | | | 5 | 32 | | | | Round/Hexagon/Square/Angle/Flat - - Hot Rolled and Bright Bars |

**Remarks**

+AT = solution annealed
+AR = as rolled
+M = thermo mechanical treated
+N = normalized or normalizing formed
+NT = normalized and tempered
+QT = quenched and tempered
+S = soft annealed
+SR = stress relieved

a = PMA for the use in pressure equipment in PESR 2016 as amended neccessary

TÜVRheinland®

| Scope according to | **Pressure Equipment Safety Regulations 2016 SI 2016 No.: 1105 as amended** |
|---|---|

| Material Manufacturer | | Manufacturing plant | Nationality | Date | Page No.. | |
|---|---|---|---|---|---|---|
| Company Name: | Jay Jagdamba Limited | See Page 11 | India | 20.10.23 | 4 | TUV Rheinland UK Ltd |
| Location: | Office No 405, The Landmark, Plot No. 26A, Sector 07, Kharghar, Navi Mumbai-410 210. Maharashtra, India | | | Rev.: 0 | of : 11 | |

| Cur- | Product grades (Materials-term / Materials-No.) | Product code or standard (Material Specification) | Delivery Cond. | Product Form (Article, Type of Product) | Product dimensions / quantity (Dimensions) Thickness mm from | Thickness mm Up to | ∅ mm from | ∅ mm Up to | Weight max 1=t / 2=kg ⇓ | result | Technical Specifications Requirements Technical Regulations | Original material manufacturers QMS Certificate / Remarks |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6a | 6b | 7a | 7b | 8a | 8b | 9 | 10 |
| **The use of the materials according to Pressure Equipment Safety Regulations 2016 as amended is bound to the publication of designated standards or to the particular material appraisal. With that the manufacturing reliability for equivalent material grades according to other standards (e.g. BS, AFNOR, ASME) is proved. The requirements and limits of the applicable code respectively the PESR must be observed for the use of material grades listed in column 2 to 4.** | | | | | | | | | | | | |
| 4 | 1.4301; 1.4307; 1.4401; 1.4404<br>1.4432; 1.4435; 1.4436; 1.4541<br>1.4571 | EN 10222-5 | AT | Flanges<br>Forgings | | | | | | | AD 2000 W2<br>AD 2000 W10<br>AD 2000 W13 | DN 10 to DN 1800<br>PN 6 to PN 250<br><br>½" to 72" |
| 5 | 1.0460 | EN 10222-2 | N | | | | | | | | | 150 LBS to 2500 LBS, Series A & B<br><br>OD up to 2500 mm<br>Thickness up to 400 mm |

**Remarks**

+AT = solution annealed
+AR = as rolled
+M = thermo mechanical treated
+N = normalized or normalizing formed
+NT = normalized and tempered
+QT = quenched and tempered
+S = soft annealed
+SR = stress relieved

a = PMA for the use in pressure equipment in PESR 2016 as amended neccessary

| Scope according to | **Pressure Equipment Safety Regulations 2016 SI 2016 No.: 1105 as amended** |
|---|---|

| Material Manufacturer | | Manufacturing plant | Nationality | Date | Page No.. | |
|---|---|---|---|---|---|---|
| Company Name: | Jay Jagdamba Limited | See Page 11 | India | 20.10.23 | 5 | TUV Rheinland UK Ltd |
| Location: | Office No 405, The Landmark, Plot No. 26A, Sector 07, Kharghar, Navi Mumbai-410 210. Maharashtra, India | | | Rev.: 0 | of : 11 | |

| Cur- | Product grades (Materials-term / Materials-No.) | Product code or standard (Material Specification) | Delivery Cond. | Product Form (Article, Type of Product) | Product dimensions / quantity (Dimensions) Thickness mm | | ∅ mm | | Weight max 1=t / 2=kg | | Technical Specifications Requirements Technical Regulations | Original material manufacturers QMS Certificate / Remarks |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | from | Up to | from | Up to | ⇓ | result | | |
| 1 | 2 | 3 | 4 | 5 | 6a | 6b | 7a | 7b | 8a | 8b | 9 | 10 |
| **The use of the materials according to Pressure Equipment Safety Regulations 2016 as amended is bound to the publication of designated standards or to the particular material appraisal. With that the manufacturing reliability for equivalent material grades according to other standards (e.g. BS, AFNOR, ASME) is proved. The requirements and limits of the applicable code respectively the PESR must be observed for the use of material grades listed in column 2 to 4.** | | | | | | | | | | | | |
| 6 | 1.4301; 1.4305; 1.4307; 1.4362 | | | Ingots | | | | | | | | 9"x11"x52" to 32"x38"x 74" |
| | 1.4401; 1.4404; 1.4410,1.4005 | | | Billets | | | | | | | | 400mm x 2.5mtr to 600mm x 2.5mtr |
| | 1.4432; 1.4435; 1.4436; 1.4438 | EN 10088-3 | AT | RCS | | | | | | | | 80 x 80mm to 200X200mm |
| | 1.4462; 1.4501, 1.4507, 1.4006 | | | Angle | 3 | 12.70 | | | | | | 35x35mm to 120x120mm |
| | 1.4541; 1.4542; 1.4550; 1.4571 | | | Flats | 3 | 60 | | | | | AD 2000 W2 | |
| | | | | Round Bars | | | 3 | 200 | | | AD 2000 W10 | 19.05mm to 152.4mm |
| | | | | Hex/Sq Bars | | | 5 | 100 | | | | 19.05mm to 152.4mm |
| 7 | 1.4016; 1.4021; 1.4028; 1.4031 | | | Threaded Bars | | | 5 | 60 | | | | |
| | 1.4034; 1.4057; 1.4104 | EN 10088-3 | S/QT | Wires | | | 1 | 22 | | | | |
| | | | | HRAP Coils | | | 5 | 32 | | | | Round/Hexagon/Square/Angle/Flat - - Hot Rolled and Bright Bars PMA for the use in Pressure equipment in Directive 2014/68/EU necessary |

**Remarks**

| | | | |
|---|---|---|---|
| +AT = solution annealed | +NT = normalized and tempered | a = PMA for the use in pressure equipment in PESR 2016 as amended neccessary |
| +AR = as rolled | +QT = quenched and tempered | |
| +M = thermo mechanical treated | +S = soft annealed | |
| +N = normalized or normalizing formed | +SR = stress relieved | |

| Scope according to | **Pressure Equipment Safety Regulations 2016 SI 2016 No.: 1105 as amended** |
|---|---|

| Material Manufacturer | | Manufacturing plant | Nationality | Date | Page No.. | |
|---|---|---|---|---|---|---|
| Company Name: | Jay Jagdamba Limited | See Page 11 | India | 20.10.23 | 6 | TUV Rheinland UK Ltd |
| Location: | Office No 405, The Landmark, Plot No. 26A, Sector 07, Kharghar, Navi Mumbai-410 210. Maharashtra, India | | | Rev.: 0 | of : 11 | |

| Cur- | Product grades (Materials-term / Materials-No.) | Product code or standard (Material Specification) | Delivery Cond. | Product Form (Article, Type of Product) | Product dimensions / quantity (Dimensions) Thickness mm from | Thickness mm Up to | ∅ mm from | ∅ mm Up to | Weight max 1=t / 2=kg ⇓ | Weight max result | Technical Specifications Requirements Technical Regulations | Original material manufacturers QMS Certificate / Remarks |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6a | 6b | 7a | 7b | 8a | 8b | 9 | 10 |
| **The use of the materials according to Pressure Equipment Safety Regulations 2016 as amended is bound to the publication of designated standards or to the particular material appraisal. With that the manufacturing reliability for equivalent material grades according to other standards (e.g. BS, AFNOR, ASME) is proved. The requirements and limits of the applicable code respectively the PESR must be observed for the use of material grades listed in column 2 to 4.** | | | | | | | | | | | | |
| 8 | F304/F304H/F304L/F310/F310H<br>F316/F316H/F316L<br>F316N/ F316LN/F316Ti/ F317L<br>F321/F321H/F316Ti/F347/<br>F51/F53/F55/F60 | ASTM A 182 | AT | Ingots<br>Billets<br>RCS<br>Round Bars | | | 3 | 200 | | | | 9"x11"x52" to 32"x38"x 74"<br>400mm x 2.5mtr to 600mm x 2.5mtr<br>80 x 80mm to 200X200mm<br>35x35mm to 120x120mm<br>19.05mm to 152.4mm |
| 9 | F5/F9/F11/F12/F22/F91 | ASTM A 182 | S/N/NT | Flanges<br>Forgings | | | | | | | | 19.05mm to 152.4mm |
| 10 | F6a/F6NM | ASTM A 182 | Q/QT/NT | Forged Bars | | | 50 | 600 | | | | Round/Hexagon/Square/Angle/Flat |
| 11 | S17400 Type 630 | ASTM A564 | AT/SR | | | | | | | | | - - Hot Rolled and Bright Bars |
| 12 | A105 | ASTM A 105 | N | | | | | | | | | PMA for the use in Pressure equipment in Directive 2014/68/EU necessary |

**Remarks**

+AT = solution annealed
+AR = as rolled
+M = thermo mechanical treated
+N = normalized or normalizing formed
+NT = normalized and tempered
+QT = quenched and tempered
+S = soft annealed
+SR = stress relieved

a = PMA for the use in pressure equipment in PESR 2016 as amended neccessary

| Scope according to | **Pressure Equipment Safety Regulations 2016 SI 2016 No.: 1105 as amended** |
|---|---|

| Material Manufacturer | | Manufacturing plant | Nationality | Date | Page No.. | |
|---|---|---|---|---|---|---|
| Company Name: | Jay Jagdamba Limited | See Page 11 | India | 20.10.23 | 7 | TUV Rheinland UK Ltd |
| Location: | Office No 405, The Landmark, Plot No. 26A, Sector 07, Kharghar, Navi Mumbai-410 210. Maharashtra, India | | | Rev.: 0 | of : 11 | |

| Cur- | Product grades (Materials-term / Materials-No.) | Product code or standard (Material Specification) | Delivery Cond. | Product Form (Article, Type of Product) | Product dimensions / quantity (Dimensions) Thickness mm from | Thickness mm Up to | ∅ mm from | ∅ mm Up to | Weight max 1=t / 2=kg ⇓ | result | Technical Specifications Requirements Technical Regulations | Original material manufacturers QMS Certificate / Remarks |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6a | 6b | 7a | 7b | 8a | 8b | 9 | 10 |
| **The use of the materials according to Pressure Equipment Safety Regulations 2016 as amended is bound to the publication of designated standards or to the particular material appraisal. With that the manufacturing reliability for equivalent material grades according to other standards (e.g. BS, AFNOR, ASME) is proved. The requirements and limits of the applicable code respectively the PESR must be observed for the use of material grades listed in column 2 to 4.** | | | | | | | | | | | | |
| 13 | LF2 | ASTM A 350 | N | Ingots | | | | | | | | 9"x11"x52" to 32"x38"x 74" |
| 14 | 4130/4140/4340/8620 | ASTM A29 | QT | Billets<br>RCS | | | | | | | | 400mm x 2.5mtr to 600mm x 2.5mtr<br>80 x 80mm to 200X200mm<br>35x35mm to 120x120mm |
| 15 | F5/F9/F11/F22/F91 | ASME SA 336 | N/NT | Round Bars | | | 3 | 200 | | | | Round – Hot Rolled & Bright Bars |
| 16 | F304/F304L/F304H/F316/F316L<br>F316H/F321/F321H/F347/F347H | ASME SA 336 | AT | Flanges<br>Forgings<br>Forged Bars | | | 50 | 600 | | | | DN 10 to DN 1800, PN 6 to PN 250<br>½" to 72"<br>150 LBS to 2500 LBS, Series A & B<br><br>OD up to 2500 mm<br>Thickness up to 400 mm<br>PMA for the use in<br>Pressure equipment in<br>Directive 2014/68/EU necessary |

| **Remarks** | | | |
|---|---|---|---|
| | +AT = solution annealed | +NT = normalized and tempered | a = PMA for the use in pressure equipment in PESR 2016 as amended neccessary |
| | +AR = as rolled | +QT = quenched and tempered | |
| | +M = thermo mechanical treated | +S = soft annealed | |
| | +N = normalized or normalizing formed | +SR = stress relieved | |

| Scope according to | **Pressure Equipment Safety Regulations 2016 SI 2016 No.: 1105 as amended** |
|---|---|

| Material Manufacturer | | Manufacturing plant | Nationality | Date | Page No.. | |
|---|---|---|---|---|---|---|
| Company Name: | Jay Jagdamba Limited | See Page 11 | India | 20.10.23 | 8 | TUV Rheinland UK Ltd |
| Location: | Office No 405, The Landmark, Plot No. 26A, Sector 07, Kharghar, Navi Mumbai-410 210. Maharashtra, India | | | Rev.: 0 | of : 11 | |

| Cur- | Product grades (Materials-term / Materials-No.) | Product code or standard (Material Specification) | Delivery Cond. | Product Form (Article, Type of Product) | Product dimensions / quantity (Dimensions) Thickness mm from | Thickness mm Up to | ∅ mm from | ∅ mm Up to | Weight max 1=t / 2=kg ⇓ | Weight max result | Technical Specifications Requirements Technical Regulations | Original material manufacturers QMS Certificate / Remarks |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6a | 6b | 7a | 7b | 8a | 8b | 9 | 10 |
| **The use of the materials according to Pressure Equipment Safety Regulations 2016 as amended is bound to the publication of designated standards or to the particular material appraisal. With that the manufacturing reliability for equivalent material grades according to other standards (e.g. BS, AFNOR, ASME) is proved. The requirements and limits of the applicable code respectively the PESR must be observed for the use of material grades listed in column 2 to 4.** | | | | | | | | | | | | |
| 17 | 202, XM-28, 310 | ASTM A276 | AT | Ingots | | | | | | | | 9"x11"x52" to 32"x38"x 74" |
| | | | | Billets | | | | | | | | 400mm x 2.5mtr to 600mm x 2.5mtr |
| 18 | 301,302,304,304L, 316,316L | ASTM A 276 / | AT | RCS | | | | | | | | 80 x 80mm to 200X200mm |
| | 309S,310S,316Ti,321,347,317 | ASTM A 479 | | Angle | 3 | 12.70 | | | | | | 35x35mm to 120x120mm |
| | 304N,304LN, 316N,316LN | | | Flats | 3 | 60 | | | | | | |
| | | | | Round Bars | | | 3 | 200 | | | | 19.05mm to 152.4mm |
| 19 | 304H,310H,316H,321H,347H | ASTM A 479 | AT | Hex/Sq Bars | | | 5 | 100 | | | | 19.05mm to 152.4mm |
| | | | | Threaded Bars | | | 5 | 60 | | | | |
| 20 | 403,410,430,431 | ASTM A 276 / | S/QT | Wires | | | 1 | 22 | | | | |
| | | ASTM A 479 | | HRAP Coils | | | 5 | 32 | | | | Round/Hexagon/Square/Angle/Flat |
| | | | | Forged Bar | | | 50 | 600 | | | | - - Hot Rolled and Bright Bars |
| 21 | 420 | ASTM A 276 | S/QT | | | | | | | | | PMA for the use in |
| | | | | | | | | | | | | Pressure equipment in |
| 22 | 17-4PH (Type 630) | ASTM A 564 | AT/SR | | | | | | | | | Directive 2014/68/EU necessary |

**Remarks**

+AT = solution annealed
+AR = as rolled
+M = thermo mechanical treated
+N = normalized or normalizing formed
+NT = normalized and tempered
+QT = quenched and tempered
+S = soft annealed
+SR = stress relieved

a = PMA for the use in pressure equipment in PESR 2016 as amended neccessary

TÜVRheinland®

| Scope according to | **Pressure Equipment Safety Regulations 2016 SI 2016 No.: 1105 as amended** |
|---|---|

| Material Manufacturer | | Manufacturing plant | Nationality | Date | Page No.. | |
|---|---|---|---|---|---|---|
| Company Name: | Jay Jagdamba Limited | See Page 11 | India | 20.10.23 | 9 | TUV Rheinland UK Ltd |
| Location: | Office No 405, The Landmark, Plot No. 26A, Sector 07, Kharghar, Navi Mumbai-410 210. Maharashtra, India | | | Rev.: 0 | of : 11 | |

| Cur- | Product grades (Materials-term / Materials-No.) | Product code or standard (Material Specification) | Delivery Cond. | Product Form (Article, Type of Product) | Product dimensions / quantity (Dimensions) Thickness mm from | Thickness mm Up to | ∅ mm from | ∅ mm Up to | Weight max 1=t / 2=kg ⇓ | Weight max result | Technical Specifications Requirements Technical Regulations | Original material manufacturers QMS Certificate / Remarks |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6a | 6b | 7a | 7b | 8a | 8b | 9 | 10 |
| **The use of the materials according to Pressure Equipment Safety Regulations 2016 as amended is bound to the publication of designated standards or to the particular material appraisal. With that the manufacturing reliability for equivalent material grades according to other standards (e.g. BS, AFNOR, ASME) is proved. The requirements and limits of the applicable code respectively the PESR must be observed for the use of material grades listed in column 2 to 4.** | | | | | | | | | | | | |
| 23 | 301 | ASTM A 240 | AT | Ingots | | | | | | | | 9"x11"x52" to 32"x38"x 74" |
| | | | | Billets | | | | | | | | 400mm x 2.5mtr to 600mm x 2.5mtr |
| 24 | 303 | ASTM A 581/ | AT | RCS | | | | | | | | 80 x 80mm to 200X200mm |
| | | ASTM A 582 | | Angle | 3 | 12.70 | | | | | | 35x35mm to 120x120mm |
| | | | | Flats | 3 | 60 | | | | | | |
| 25 | 416,430F | ASTM A 581/ | S/QT | Round Bars | | | 3 | 200 | | | | 19.05mm to 152.4mm |
| | | ASTM A 582 | | Hex/Sq Bars | | | 5 | 100 | | | | 19.05mm to 152.4mm |
| | | | | Threaded Bars | | | 5 | 60 | | | | |
| 26 | B8/B8A, B8M/B8MA, B8T/B8TA | ASTM A 193 | AT | Wires | | | 1 | 22 | | | | |
| | | | | HRAP Coils | | | 5 | 32 | | | | Round/Hexagon/Square/Angle/Flat |
| 27 | 304,304L, 316,316L,317 | ASTM A 314/ | AT | Forged Bar | | | 50 | 600 | | | | - - Hot Rolled and Bright Bars |
| | 310,310S,316Ti,321,347 | ASTM A 473 | | | | | | | | | | PMA for the use in |
| | | | | | | | | | | | | Pressure equipment in |
| 28 | 403,410,420,430,431 | ASTM A 314/ | S/QT | | | | | | | | | Directive 2014/68/EU necessary |
| | | ASTM A 473 | | | | | | | | | | |

**Remarks**

+AT = solution annealed
+AR = as rolled
+M = thermo mechanical treated
+N = normalized or normalizing formed
+NT = normalized and tempered
+QT = quenched and tempered
+S = soft annealed
+SR = stress relieved
a = PMA for the use in pressure equipment in PESR 2016 as amended neccessary

TÜVRheinland®

| Scope according to | **Pressure Equipment Safety Regulations 2016 SI 2016 No.: 1105 as amended** |
|---|---|

| Material Manufacturer | | Manufacturing plant | Nationality | Date | Page No.. | |
|---|---|---|---|---|---|---|
| Company Name: | Jay Jagdamba Limited | See Page 11 | India | 20.10.23 | 10 | TUV Rheinland UK Ltd |
| Location: | Office No 405, The Landmark, Plot No. 26A, Sector 07, Kharghar, Navi Mumbai-410 210. Maharashtra, India | | | Rev.: 0 | of : 11 | |

| Cur- | Product grades (Materials-term / Materials-No.) | Product code or standard (Material Specification) | Delivery Cond. | Product Form (Article, Type of Product) | Product dimensions / quantity (Dimensions) Thickness mm | | ∅ mm | | Weight max 1=t / 2=kg | | Technical Specifications Requirements Technical Regulations | Original material manufacturers QMS Certificate / Remarks |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | from | Up to | from | Up to | ⇓ | result | | |
| 1 | 2 | 3 | 4 | 5 | 6a | 6b | 7a | 7b | 8a | 8b | 9 | 10 |
| **The use of the materials according to Pressure Equipment Safety Regulations 2016 as amended is bound to the publication of designated standards or to the particular material appraisal. With that the manufacturing reliability for equivalent material grades according to other standards (e.g. BS, AFNOR, ASME) is proved. The requirements and limits of the applicable code respectively the PESR must be observed for the use of material grades listed in column 2 to 4.** | | | | | | | | | | | | |
| 29 | 1.4057,1.4006,1.4021 | EN 10250-4 | S/QT | Flanges<br>Forgings | | | | | | | | DN 10 to DN 1800<br>PN 6 to PN 250 |
| 30 | SA266 Gr2/Gr4 | ASME SA 266 | N/NT | Forged Bar | | | 50 | 600 | | | | ½" to 72"<br>150 LBS to 2500 LBS, Series A & B<br><br>OD up to 2500 mm<br>Thickness up to 400 mm<br><br>PMA for the use in pressure equipment in Directive 2014/68/EU necessary |

**Remarks**

+AT = solution annealed
+AR = as rolled
+M = thermo mechanical treated
+N = normalized or normalizing formed
+NT = normalized and tempered
+QT = quenched and tempered
+S = soft annealed
+SR = stress relieved
a = PMA for the use in pressure equipment in PESR 2016 as amended neccessary

**Works Address**

**1A. .JAY JAGDAMBA LIMITED**
**Works1**: Gut No.92/3, 422, 423, 424, 44, 45, 46/1, 46/2(P) and 58/2
Village Abitghar, Shirispada- Shahapur Road, Taluka Wada,Dist.Palghar-421 303, Maharashtra, India

**2A. JAY JAGDAMBA PROFILE PRIVATE LIMITED**
**Works 2**: Gut No. 44(P), 46/2(P) and 60(P),
Village Abitghar, Shirispada- Shahapur Road, Taluka Wada,Dist.Palghar-421 303, Maharashtra, India.

**3A. JAY JAGDAMBA FORGINGS PRIVATE LIMITED**
**Works 3:** Gut No.39/1(P) and 44(P)
Village Abitghar, Shirispada- Shahapur Road, Taluka Wada,
Dist.Palghar-421 303, Mahrashtra, India.

**4A. SHREE JAY JAGDAMBA FLANGES PRIVATE LIMITEDWorks 4**: Gut No.39/1(P), 44(P), 46/2(P), 61 and 66(P)
Village Abitghar, Shirispada- Shahapur Road, Taluka Wada,Dist.Palghar-421 303, Mahrashtra, India.